

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

(19)



(11) Publication number: **58175851**

Generated Document.

PATENT ABSTRACTS OF JAPAN

(21) Application number: **58044202**

(51) Intl. Cl.: **H01L 23/44**

(22) Application date: **18.03.83**

(30) Priority:

(43) Date of application
publication: **15.10.83**

(84) Designated contracting
states:

(71) Applicant: **HITACHI LTD**

(72) Inventor: **AKIYAMA HIROYUKI**
ITAHANA HIROSHI

(74) Representative:

(54) **ENCLOSED TYPE BOILING COOLER**

(57) Abstract:

PURPOSE: To obtain the header part of the cooler being light weight and having mechanical intensity enabling to endure pressure in a vessel by a method wherein the shape of the header part is improved.

CONSTITUTION: The enclosed boiling cooler is constructed as to communicate between an evaporator 3 accommodating a semiconductor 1 and being filled up with a coolant 2 as to dip the semiconductor 1, and a condenser to condense the evaporated coolant. The condenser is consisting of condensing pipes 5 of the plural number and the header parts 4 communicating the fellow condensing pipes 5, and thermally radiating fins 6 are equipped to the condensing pipes 5. Out of two sheet plates constituting the header part 4, the condensing pipes 5 are welded through the plate 11 on the inside, and moreover the plate 12 on the outside is welded by the whole circumference thereof to the plate 11 on the inside. The plates 11, 12 have the concave parts and the convex parts, and the fellow convex parts are

made to come in contact mutually,
and are joined mutually by employing
plug welding, etc.

COPYRIGHT: (C)1983,JPO&Japio

